OSRAM

LEDriving HLM EASY HS1



Cool White color temperature of 6,000 K

Better visibility thanks to daylight effect



Superior brightness

Allowing a high compatibility and an easy installation.



LED replacement for conventional HS1 high and low beam lamps

Reduced glaring thanks to an optimal light distribution



LED high and low beams lamps with plug & play system for motorcycles.

The OSRAM LEDriving HLM EASY represent an easy solution to upgrade conventional motorcycle headlights with cool white LED light – with a color temperature of 6,000 K, they provide a stylish and modern look as well as superior brightness. Equipped with the latest LED technology and a very compact design, these lamps allow high compatibility and an easy installation for a wide range of motorcycle models. The LEDriving HLM EASY lamps are 12V and AC/DC compatible and offer a long service life. These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Product datasheet

Technical data

Product information

Product type (off-road vs. on-road)	Off-road ≙ HS1	
Application (Category and Product specific)	Mainly used for headlight applications	

General Product Information

Electrical Data

Power input	6.0 W / 5.0 W	
Nominal voltage	12.0 V	
Nominal wattage	5 W	
Test voltage	13.2 V	
Power input tolerance	±10 %	

Photometric Data

Nominal luminous flux	650/500 lm	
Luminous flux tolerance	±15 %	
Color temperature	6000 K	
Light color LED	Cool white	

Physical Attributes & Dimensions

Length	88.0 mm
Diameter	21.0 mm
Product weight	33.00 g
Lamp base	PX43t

Lifetime Data

Lifespan B3	500 hr
Lifespan Tc	1000 hr

Capabilities

Technology	LED
reamotogy	

Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)		
Date of declaration	09-07-2024	

Product datasheet

Primary article identifier	4062172345521 4062172399869	
Declaration no. in SCIP database	In work	

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172345538	LEDriving HLM EASY		- x - x -	2.52 dm ³	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Legal advice

These products do not have ECE approval and must not be used on public roads in any exterior application. Public roads use leads to cancellation of operating license and loss of insurance coverage. Several countries forbid sale and use of these products. Please contact your local distributor for further information.

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

