OSRAM

LEDriving Universal Headlights





4 function Universal Headlight

Maximum flexibility and a wide range of possible applications



Brilliantly white light with up to 6500K

Exceptional illumination, performance, quality, shape, durability and functionality



IP & IK protection classes

Tested and validated in a DIN-certified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more



2 years OSRAM guarantee1)

Powerful performance and exceptionally long service life

Product family datasheet





Individual light for individual requirements

Experience maximum flexibility and a wide range of possible applications with the OSRAM LEDriving Universal Headlights. The Bi-LED modules seamlessly integrate both low beam and high beam functionalities into a single headlamp module, providing you with the option for additional position light and daytime running light functions based on your requirements. They are available for left-hand drive (LEDUHL101/LEDUHL103) and right-hand drive (LEDUHL102/LEDUHL104). The four headlights in total offer superior illumination, performance, and quality. They are designed to deliver a brilliantly white light with exceptional clarity, ensuring enhanced visibility on the road. With their durable construction and sleek design, the headlights combine both style and functionality. The Universal Headlights are suitable for 12V and 24V vehicles and come in four different variants with a wide range of applications: the basic functions of low beam or high beam can be combined with other functions such as daytime running light and position light. Additionally, OSRAM has developed a specially designed mounting kit for easy, uncomplicated and flexible assembly. The LEDriving Mounting Kit MK1 comes with a mounting plate, screws, clips and inserts and offers three mounting options: direct mount, mount with a mounting plate, and optional mount with a leveling motor. This allows for easy adaptation to different vehicle types. When it comes to external influences, the Universal Headlights are built to withstand extreme conditions. They are resistant to water, dust, shocks, vibrations, and a wide range of temperatures (validated according to the highest IP & IK protection classes IP6K7 & IP6K9K). Trust in quality and performance - OSRAM LEDriving Universal Headlights are proudly made in Europe, meet the highest standards and have a 2-year OSRAM quarantee1).1)For precise conditions refer to: www.osram.com/am-guarantee

Product family datasheet

Technical data

	Product information	General Product		Electrical Data			
Product description	Application (Category and Product specific)	Global order reference		Nominal voltage		Nominal wattage	
LEDriving Universal Headlight 101- 102	Headlights	LEDUHL101- LEDUHL102		12/24 V		33 W	
LEDriving Universal Headlight 103- 104	Headlights	LEDUHL103- LEDUHL104		12/24 V		28 W	
	Photometric Data	Lifetime Data			Logistical data		
Product description	Nominal luminous flux	Guarantee	Type of p	Type of protection		Commodity code	
LEDriving Universal Headlight 101- 102	780-1180 lm	2 years	IP6K9K/I	P6K7	85122000900		
LEDriving Universal Headlight 103- 780-1180 lm 104		2 years	IP6K9K/I	P6K7	85122000900		
	Environmental & Regulatory Information Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACh)						
Product description	Declaration no. in SCIP database						
LEDriving Universal Headlight 101- 102	In work						
LEDriving Universal Headlight 103- 104	In work						

Product family datasheet

Download Data

	File
7	User instruction LEDriving UNIVERSAL HEADLIGHT, LEDriving UNIVERSAL HEADLIGHT
D	Movie application LEDriving Universal Headlights LEDUHL Produkt Video DE
•	Movie application LEDriving Universal Headlights LEDUHL Product Video EN

Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

Legal advice

1)For precise conditions refer to: www.osram.com/am-guarantee

Application advice

For more detailed application information and graphics please see product datasheet.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.