

# Lightbar FX750-CB SM GEN 2



**Single mount certified**  
For individual installation



**Up to 450 m long beam**  
Improved far and near field illumination



**Combo Beam**  
In combination: Coverage of near and far field illumination



**IP & IK protection classes**  
Tested and validated in a DIN-certified environmental simulation laboratory regarding extreme external influences such as water, dust, shocks, impacts, heat, cold, permanent vibrations and many more

## Product family datasheet



### Increased brightness for far and near field illumination

Particularly when driving on rural and dirt roads, a greater range of visibility can play a key role in ensuring safety. The LEDriving Lightbar FX750-CB SM GEN 2 provides additional, near and far field illumination on dark roads with up to 5.990 Lumen. Even in poor visibility conditions or at dusk, the 25 high-performance LEDs reach a light distance of up to 450 meters and daytime lighting conditions with a color temperature of 6000 Kelvin. The driving light impresses with its special reflector design and ensure not only a modern and appealing look but also reduces glare for more visibility on the road. It can be used as both a supplementary LED high beam headlight and a powerful working light. The light is fully ECE-compliant in both versions and therefore suitable for use on roads. Additionally, OSRAM has developed a specially designed mounting kit, compatible with all driving lights of the Functional series FX Gen 2 for individual mounting. Versatile applicable, it defies numerous environmental influences and, thanks to high-quality materials such as the aluminum housing and the stable polycarbonate lens, it is particularly light and at the same time robust and resistant. Complete polarity protection both prevents damage from excess voltage and contributes to a longer lifespan. The LEDriving Lightbar FX750-CB SM GEN 2 has been tested and validated with the IP-Protection Classes IP6K8 & IP6K9K in our DIN certified environmental simulation laboratory for extreme external influences regarding water, dust, impacts, heat, cold and permanent vibration. Its variability gives the FX series a flexible range of uses. They can be attached to cars, trucks, agricultural machinery, commercial vehicles, construction vehicles, caravans, off-road vehicles and quads<sup>1)</sup>. OSRAM provides a 5-year guarantee<sup>2)</sup>.<sup>1)</sup> OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed. <sup>2)</sup> For precise conditions refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

## Product family datasheet

### Technical data

|  | Product information  | General Product Information | Electrical Data | Photometric Data      |
|--|--|-----------------------------|-----------------|-----------------------|
| Product description                          | Application (Category and Product specific)                                      | Global order reference      | Nominal wattage | Nominal luminous flux |
| Lightbar FX750-CB SM GEN 2<br>LEDDL133-CB SM | Driving Light -<br>Additional high beam<br>application - central<br>single mount | LEDDL133-CB SM              | 94 W            | 5990 lm               |

|  | Lifetime Data | Capabilities      | Certificates & standards  |                    |               |
|--|---------------|-------------------|---------------------------|--------------------|---------------|
| Product description                          | Lifespan Tc   | Technology        | Approval marks – approval | Type of protection | Standards     |
| Lightbar FX750-CB SM GEN 2<br>LEDDL133-CB SM | > 5000<br>hr  | LED <sup>1)</sup> | E57 approval              | IP6K8/IP6K9K       | R10, 2 x R149 |

|  | Logistical data | Environmental & Regulatory Information<br>Information according Art. 33 of EU<br>Regulation (EC) 1907/2006 (REACH) |                                     |
|--|-----------------|--|-------------------------------------|
| Product description                          | Commodity code  | Date of declaration  | Declaration no. in<br>SCIP database |
| Lightbar FX750-CB SM GEN 2<br>LEDDL133-CB SM | 85122000900     | 06-09-2024   | In work                             |

<sup>1)</sup> Light-emitting diode application

## Product family datasheet

### Safety advice

For detailed application information, please refer to the product data sheet and the user instruction

### Legal advice

1) OSRAM LEDriving Driving Lights are approved according to ECE regulations and may therefore be installed and operated on public roads. Please note: Special installation regulations apply. In addition to ECE approval of the product, individual special requirements and legislation of the countries must be observed.2) For precise conditions please refer to: [www.osram.com/am-guarantee](http://www.osram.com/am-guarantee)

### Application advice

For more detailed application information and graphics please see product datasheet.

### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.