

# XENARC NIGHT BREAKER 220 D4S



**Up to 220% more brightness<sup>1)1)</sup>  
Compared to minimum ECE R98R99.  
requirements.**

More light allows to see farther and therefore react sooner compared to the minimum legal standard



**Up to 250 m long beam**

For better visibility



**Up to 20% whiter light<sup>1)1)</sup> Compared to  
minimum ECE R98R99 requirements.**

More modern look compared to the minimum legal standard



### The most powerful xenon light from OSRAM

XENARC NIGHT BREAKER 220 is the brightest OSRAM xenon light. This powerful lamp with efficient xenon technology ensures a better visibility on the road: up to 220% more brightness compared to the minimum legal standard. More light allows to see further and therefore react sooner. Added to this is the up to 250 meter long beam and up to 20% whiter light for more modern look (compared to the minimum legal standard). Discover the pure performance of XENARC NIGHT BREAKER 220 - the most powerful xenon light from OSRAM, available in D1S, D2S, D3S and D4S. Please note: XENARC lamp change is recommended to be carried out by a professional and in pairs.

# Product datasheet

## Technical data

### Electrical Data

Power input	35 W
Nominal voltage	42.0 V
Nominal wattage	35 W
Power input tolerance	±3 %
Test voltage	13.5 V

### Photometric Data

Nominal luminous flux	3200 lm
Luminous flux tolerance	±15 %

### Physical Attributes & Dimensions

Lamp base	P32d-5
Length	77.3 mm
Diameter	9 mm
Product weight	16.30 g

### Lifetime Data

Lifespan B3	2000 hr
Lifespan Tc	3000 hr

### Capabilities

Technology	HID <sup>1)</sup>
------------	-------------------

<sup>1)</sup> High-intensity discharge lamp

### Certificates & standards

ECE category	D4S <sup>1)</sup>
--------------	-------------------

<sup>1)</sup> To be operated only with approved electronic control gear

### Environmental & Regulatory Information

Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of declaration	09-07-2024
Primary article identifier	4062172398701   4062172397827
Declaration no. in SCIP database	In work


## Logistical Data

## Product datasheet

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4062172397834	XENARC NIGHT BREAKER 220 D4S		- x - x -	1.68 dm <sup>3</sup>	
4062172398718	XENARC NIGHT BREAKER 220 D4S		- x - x -	1.20 dm <sup>3</sup>	

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

### Download Data

File
 ref_pim_amsproduct360degreeimages XENARC NIGHT BREAKER D4S 66440XNB

#### Safety advice

XENARC lamps should be replaced by a qualified mechanicThis product must only be operated with approved electronic control gear

#### Legal advice

Light output compared to the minimum ECE R112/R37 requirementsThis product must only be operated with approved electronic control gearXENARC lamps should be replaced by a qualified mechanicReduced UV emission | For projection headlights | ECE approval and DOT label≠ 450 lm

#### Application advice

For more detailed application information and graphics please see product datasheet.

#### Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

# OSRAM